

Glass Beads Sterilizer

DRYING OVEN

LABORATORY
INCUBATOR

MUFFLE FURNACE

WATER DISTILLER

WATER BATH
& OIL BATH

HEATING MANTLE

STIRRER

MIXER & SHAKER

HEATING PLATE &
SAND BATH

DIGESTION APPARATUS
& METAL BATH

NITROGEN SAMPLE
CONCENTRATOR

CLEAN BENCH

STERILIZER

VACUUM PUMP

FILTRATION

GRINDER

COLONY COUNTER

DRYER

CENTRIFUGE

ELECTRIC FURNACE

LIFTING TABLE

LABORATORY
CONSUMABLE



GBS series rapid glass bead sterilizer is a product that uses high temperature glass beads to quickly sterilize small experimental equipment. It can effectively disinfect and sterilize small solid metal and glass utensils within ten seconds, efficiently eliminate bacteria and spores, and can be used for surgical forceps, scissors, tweezers, scalpels, needles, vaccination rings and vaccination needles, etc., often used in scientific research laboratories.



Scientific Research



Agriculture



Food Processing



Husbandry Scientific Research

DRYING OVEN

Characteristics:

LABORATORY INCUBATOR

- Stainless steel container with high performance heating element, high precision temperature controller and overtemperature protection.
- The maximum temperature in the container containing high temperature sterilized beads can be heated to about 300°C.

MUFFLE FURNACE

- LED display real-time temperature, temperature can be set.
- Blinking indicator indicates that the instrument is running to the set temperature, the indicator light indicates constant temperature, and the indicator light does not indicate that the operation is stopped.

WATER DISTILLER

- Small size, light weight, easy operation, long service life.

WATER BATH & OIL BATH

HEATING MANTLE

Major Technical Parameters:

STIRRER

MIXER & SHAKER

HEATING PLATE & SAND BATH

DIGESTION APPARATUS & METAL BATH

NITROGEN SAMPLE CONCENTRATOR

CLEAN BENCH

STERILIZER

VACUUM PUMP

FILTRATION

GRINDER

COLONY COUNTER

DRYER

CENTRIFUGE

ELECTRIC FURNACE

LIFTING TABLE

LABORATORY CONSUMABLE

Model	GBS-80	GBS-150
Working Room Size	Φ40*80	Φ40*150
Capacity (g)	300	600
Temperature range (°C)	100-300	
Temperature control accuracy (°C)	< ±5	
Maximum temperature time (min)	≤25	
Timing range (min)	0-999	
Power (W)	120	300
Voltage	110/220V	
Overall Dimensions (L*W*H) (mm)	160*190*250	
NW(KG)	4.3	
Material	Mirror stainless steel	
Safety Device	Overtemperature protection	
Additional Function	Temperature can be set	