

Orbital Shaker



DRYING OVEN

LABORATORY INCUBATOR

MUFFLE FURNACE

WATER DISTILLER

WATER BATH & OIL BATH

HEATING MANTLE

STIRRER

MIXER & SHAKER

HEATING PLATE & SAND BATH

DIGESTION APPARATUS & METAL BATH

NITROGEN SAMPLE CONCENTRATOR

CLEAN BENCH

STERILIZER

VACUUM PUMP

FILTRATION

GRINDER

COLONY COUNTER

DRYER

CENTRIFUGE


ELECTRIC FURNACE

LIFTING TABLE

LABORATORY CONSUMABLE

Brushless DC motor

The motor is maintenance-free, can work continuously for a long time has strong power, low noise, large torque, and stable starting.



DRYING OVEN

LABORATORY INCUBATOR

MUFFLE FURNACE

WATER DISTILLER

WATER BATH & OIL BATH

HEATING MANTLE

STIRRER

MIXER & SHAKER

HEATING PLATE & SAND BATH

DIGESTION APPARATUS & METAL BATH

NITROGEN SAMPLE CONCENTRATOR

CLEAN BENCH

STERILIZER

VACUUM PUMP

FILTRATION

GRINDER

COLONY COUNTER

DRYER

CENTRIFUGE

ELECTRIC FURNACE

LIFTING TABLE

LABORATORY CONSUMABLE

The Orbital Shaker is suitable for a variety of mixing work in different fields. It adopts DC brushless motor technology and microcomputer control technology, integrates humanized design, easy to operate, and is suitable for biology, microbiology and medical analysis and other fields. Low energy consumption, safety, stability and no noise.



Laboratory



Science education



Biological research



Medical science

Characteristics:

- Adjustable speed, diverse functions, moderate vibration suitable for a variety of mixed work
- LCD touch control system in different fields, can set and display the number of revolutions, time.
- The program can be run at the same time to set different revolutions and time.
- Timing conversion system can complete the switch between seconds, minutes and hours.

DC brushless motor drive, long life, maintenance-free, quiet and stable no noise. 6.The platform can be replaced with different containers, with conical flask rack, adjustable flask rack, universal tray, spring tray to choose

Major Technical Parameters:

DRYING OVEN

LABORATORY INCUBATOR

MUFFLE FURNACE

WATER DISTILLER

WATER BATH & OIL BATH

HEATING MANTLE

STIRRER

MIXER & SHAKER

HEATING PLATE & SAND BATH

DIGESTION APPARATUS & METAL BATH

NITROGEN SAMPLE CONCENTRATOR

CLEAN BENCH

STERILIZER

VACUUM PUMP

FILTRATION

GRINDER

COLONY COUNTER

DRYER

CENTRIFUGE





ELECTRIC FURNACE

LIFTING TABLE

LABORATORY CONSUMABLE

Model	OS-10	OS-20	OS-30
Shaking Mode	Horizontal rotation		
Motor type	Brushless DC Motor		
Controller type	LCD Touch Screen Programmable controller		
Timing Range	1s-999h		
Speed Range	50-350rpm	50-300rpm	50-250rpm
Diameter of Orbit	10mm	20mm	30mm
Max load	3KGS		
Voltage	AC90-240V 50-60Hz		
Power	50W		
Programmable segment	20		
Size of Plate (L*W*H) (mm)	275*225		
Size of Exterior (L*W*H) (mm)	285*290*130		

Optional Accessories Major Technical Parameters:

PB1	PB2	12*100	6*250	AU-1	AN-2
					
Non-slip mat	Double Non-slip mat	12xConical flask holder (100-150ml)	6xConical flask holder (200-300ml)	Adjustable flask holder	Universal spring bracket