

DRYING OVEN

LABORATORY INCUBATOR

MUFFLE FURNACE

WATER DISTILLER

WATER BATH &OIL BATH

HEATING MANTLE

STIRRER

MIXER & SHAKER

HEATING PLATE & SAND BATH

DIGESTION APPARATUS & METAL BATH

NITROGN SAMPLE CONCENTRATOR

CLEAN BENCH

STERILIZER

VACUUM PUMP

FILTRATION

GRINDER

COLONY COUNTER

DRYER

CENTRIFUGE

ELECTRIC FURNACE

LIFTING TABLE

LABORATORY CONSUMABLE



MIX-28 MIX-28 MIX-28+





DRYING OVEN

LABORATORY INCUBATOR

MUFFLE FURNACE

WATER DISTILLER

WATER BATH &OIL BATH

HEATING MANTLE

STIRRER

MIXER & SHAKER

HEATING PLATE & SAND BATH

DIGESTION APPARATUS & METAL BATH

NITROGN SAMPLE CONCENTRATOR

CLEAN BENCH

STERILIZER

VACUUM PUMP

FILTRATION

GRINDER

COLONY COUNTER

DRYER

CENTRIFUGE

ELECTRIC FURNACE

LIFTING TABLE

LABORATORY CONSUMABLE

Characteristics:

• The maximum diameter of the mixed tube is up to 30mm. Suit for mixing tubes / centrifugal tubes with prominent mixing effect. The Outer shell and touch concave are made of plastic which is resistance to chemical attack. The thick base makes operation very steady and reliable. 12V low voltage power adapter built in, very smart and portable.

Major Technical Parameters:

Model	MIX-28	MIX-28+
Control method	Knob speed regulation	Constant speed
Shaking Orbit	4.5mm(circle)	
Loading Capacity	50ml	
Shaking speed	2800rpm	Start-2800rpm
Voltage	AC90 - 230V 15W	
Motor Input Power	1.2W	
Motor Output Power	0.8W	
Allowable ambient temperature	50 ~ 40°C, 80%RH	
Enclosure protection level	IP42	
Size of Exterior (L*W*H) (mm)	110*126*80	
NW (KG)	1.2	
GW (KG)	1.4	